


15/20/25/30W KS-MD03R-A-415

Simple but exquisite square mounted downlight combines aesthetic features and performance. High quality and special painting meet high standard demands. High quality optical material, famous brand CREE LED chip, professional lighting design with appropriate color, all these make the great lighting effect.

- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



General

Dimensions	100*100*145mm
Installation	Surface Mounted
Beam Angle	15° 24° 30° 36° 60°
Voltage	AC220-240V
Certification	CE, ROHS
Warranty	3 Years

Performance

Colour Rendering	Ra>80/90
Longevity	50,000 hours
System Power	15 W 20 W 25 W 30 W
Exit Lumens	1200 lm 1600 lm 2000 lm 2400 lm
Efficiency	80.0 lm/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Carbon Allowance) SKA Rating

LEDUK

15/20/25/30W KS-MD03R-A-415

Available options

Wattage	15W - 1200 lm, 20W - 1600 lm, 25W - 2000 lm, 30W - 2400 lm
Beam Angle	15°, 24°, 30°, 36°, 60°
Colour	3000K, 4000K, 5000K
Dimming	Fixed Output, 1-10V Dimming, DALI Dimmable

Product Code: 15/20/25/30W KS-MD03R-A-415