

LED UK

20/25/30W KAS-TL09R-A-8020

Angular body design, powerful heat sink which can breath, three kinds of install way, high brightness highlighting the objects. Patent breath heat sink protects the light from over heat, ensuring long life span. 360° Rotation, and 0°-90° tilt. Finish Color: Black/White/Silver, Special color can be customized.

- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



General

Dimensions	164mm*130mm*80mm
Installation	Track Lighting
Beam Angle	15° 20° 30° 36° 45°
Voltage	AC220-240V
Certification	CE, ROHS
Warranty	3 Years

Performance

Colour Rendering	Ra>80/90
Longevity	50,000 hours
System Power	20 W 25 W 30 W
Exit Lumens	1800 lm 2250 lm 2700 lm
Efficiency	90.0 ll/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Carbon Allowance) SKA Rating

Available options

Wattage	20W - 1800 lm, 25W - 2250 lm, 30W - 2700 lm
Beam Angle	15°, 20°, 30°, 36°, 45°
Colour	3000K, 4000K, 5000K
Base Colour	White, Iron gray
Dimming	Fixed Output, 1-10V Dimming, DALI Dimmable

Product Code: 20/25/30W KAS-TL09R-A-8020