

LED UK

20/25/30W KAS-TL11R-B-8020

Simple and delicate, flexibly adjustable angle let you emphasize the lighting project freely, showing you the perfect spot. Top-mounted, side-mounted and recessed spot light with smooth body painting. 360° Rotation, and 0°-90° tilt. Finish Color: Black/White/Silver, Special color can be customized

- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span

General

Dimensions	80*162*180mm
Installation	Track Lighting
Beam Angle	20° 24° 30° 36° 45°
Voltage	AC220-240V
Certification	CE, ROHS
Warranty	5 Years



Performance

Colour Rendering	Ra>80/90
Longevity	50,000 hours
System Power	20 W 25 W 30 W
Exit Lumens	1800 lm 2250 lm 2700 lm
Efficiency	90.0 ll/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Carbon Allowance) SKA Rating

Available options

Wattage	20W - 1800 lm, 25W - 2250 lm, 30W - 2700 lm
Beam Angle	20°, 24°, 30°, 36°, 45°
Colour	3000K, 4000K, 5000K
Base Colour	White, Black, Silver
Dimming	Fixed Output, 1-10V Dimming, DALI Dimmable

Product Code: 20/25/30W KAS-TL11R-B-8020