

# LED UK

## 20/30W KS-MD02D-A-820

---

Simple but exquisite, our mounted downlight combines aesthetic features and performance. A variety of choices and customized services depending on your requirements. A professional design with high quality optical materials including an AL1090 aluminum reflector for COB and a fire rated PC for SMD ensures high light transmission, uniform light beam and excellent light quality. even and soft light offers a desirable lighting atmosphere.

- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



### General

|               |                 |
|---------------|-----------------|
| Dimensions    | 195mm*130mm     |
| Installation  | Surface Mounted |
| Beam Angle    | 90°             |
| Voltage       | AC220-240V      |
| Certification | CE, ROHS        |
| Warranty      | 3 Years         |

### Performance

|                  |                                                                                                        |
|------------------|--------------------------------------------------------------------------------------------------------|
| Colour Rendering | Ra>80                                                                                                  |
| Longevity        | 50,000 hours                                                                                           |
| System Power     | 20 W<br>30 W                                                                                           |
| Exit Lumens      | 1600 lm<br>2400 lm                                                                                     |
| Efficiency       | 80.0 lm/cW                                                                                             |
| Compliance       | Building Regulations<br>ETL (Energy Technology List)<br>ECA (Enhanced Capital Allowance)<br>SKA Rating |

### Available options

|         |                                            |
|---------|--------------------------------------------|
| Wattage | 20W - 1600 lm, 30W - 2400 lm               |
| Colour  | 3000K, 4000K, 5000K                        |
| Dimming | Fixed Output, 1-10V Dimming, DALI Dimmable |

**Product Code: 20/30W KS-MD02D-A-820**