

## 20/30W KS-MD02R-A-820

Simple but exquisite, our mounted downlight combines aesthetic features and performance. A variety of choices and customized services depending on your requirements. A professional design with high quality optical materials including an AL1090 aluminum reflector for COB and a fire rated PC for SMD ensures high light transmission, uniform light beam and excellent light quality. even and soft light offers a desireable lighting atmosphere.

- Instant on no flicker
- Environmentally Friendly No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



## General

Dimensions	200mm*139mm
Installation	Surface Mounted
Beam Angle	90°
Voltage	AC220-240V
Certification	CE, ROHS
Warranty	3 Years

## **Performance**

Colour Rendering	Ra>80/90
Longevity	50,000 hours
System Power	20 W 30 W
Exit Lumens	1600 lm 2400 lm
Efficiency	80.0 II/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

## **Available options**

Wattage	20W - 1600 lm, 30W - 2400 lm
Colour	3000K, 4000K, 5000K
Dimming	Fixed Output, 1-10V Dimming, DALI Dimmable

Product Code: 20/30W KS-MD02R-A-820