

## 8/10W KAS-BL10R-308

Narrow trim full-closed series, with the driver fixed inside. Its window design makes it well-ventilated. White trim integrates the light with ceiling, clean and fashionable. Full-closed style with window design achieves active heat dissipation. The installation clips protect the ceiling and offer a convenient and easy installation. The mini cap on the bottom of the heatsink ensures that safety standards are met.

- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



### General

<b>Dimensions</b>	93mm*93mm*135mm
<b>Cut Out</b>	85mm*85mm
<b>Installation</b>	Recessed
<b>Beam Angle</b>	15° 20° 30° 36° 60°
<b>Voltage</b>	AC220-240V
<b>Certification</b>	CE, ROHS
<b>Warranty</b>	3 Years

### Performance

<b>Colour Rendering</b>	Ra>80/90
<b>Longevity</b>	50,000 hours
<b>System Power</b>	8 W 10 W
<b>Exit Lumens</b>	640 lm 800 lm
<b>Efficiency</b>	80.0 ll/cW
<b>Compliance</b>	Building Regulations ETL (Energy Technology List) ECA (Enhanced Carbon Allowance) SKA Rating

### Available options

<b>Wattage</b>	8W -640 lm, 10W - 800 lm
<b>Beam Angle</b>	20°, 24°, 30°, 36°, 60°
<b>Colour</b>	3000K, 4000K, 5000K
<b>Base Colour</b>	White, Iron Gray
<b>Dimming</b>	Fixed Output, 1-10V Dimming, DALI Dimmable

**Product Code: 8/10W KAS-BL10R-308**