

8W KAS-CL18R-308F

High power and high intensity LED module, combined with patent design optic lens to provide high quality light ray and various options of color temperature create elegant space and superior lighting effect. Unique patent design anti-glare function of our LED ceiling light creates a gentle light comfortable to the eyes. 30deg cut-off angle ensures glare protection. Its high taste narrow trim or trimless design and stack-effect heat sink which is sufficient for cooling ensure the long life span of the light, gives you a more elegant and nicer ceiling.

- CREE LED Engine
- Cast Aluminium
- · Instant on no flicker
- Environmentally Friendly No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



General

Dimensions	73*73*103mm
Cutout	75*75mm
Installation	Ceiling Tile Plasterboard
Beam Angle	15° 24° 30° 36° 60°
Voltage	AC220-240V
Certification	CE, ROHS
Warranty	3 Years

Performance

Colour Rendering	Ra>80
Longevity	50,000 hours
System Power	8 W 10 W
Exit Lumens	640 lm 800 lm
Efficiency	80.0 II/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Carbon Allowance) SKA Rating



Available options

Wattage	8 W - 640 lm, 10 W - 800 lm
Colour	3000K, 4000K, 5000K
Beam Angle	15° Beam, 24° Beam, 30° Beam, 36° Beam, 60° Beam
Dimming	Fixed Output, 1-10V Dimming, DALI Dimmable

Product Code: 8W KAS-CL18R-308F