

LED UK

Aether

The Aether is a IP65 high bay LED with options of 100W, 120W, 150W and 200W outputs, each with high efficiency at 165 ll/cW. This luminaire is designed for very high ambient temperatures due to its large heatsink ensuring excellent heat dissipation performance. The body is made from cast aluminium and houses a tempered glass diffuser. The Aether comes supplied with either a ceiling mounting bracket or loop suspension mounting.



- Nichia LED chip
- Aluminium body and tempered glass diffuser
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span

General

Dimensions	Ø400x306.5mm
Weight	8.0 kg
Voltage	220-240Vac 50/60Hz
Certification	CE, ROHS
Warranty	5 Years
IP Rating	IP65

Performance

Colour Rendering	Ra>70
Longevity	50,000 hours
Power	100 W 120 W 150 W 200 W
Exit Lumens	16,500 lm 19,800 lm 24,750 lm 33,000 lm
Efficiency	165 ll/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

Available options

Wattage	100W - 16,500lm, 120W - 19,800lm, 150W - 24,750lm, 200W - 33,000lm
Colour Temperature	3000K, 4000K, 5000K
Mounting	Suspended, Surface
Dimming	Not Required, 1-10V Dimming, DALI Dimming, Mains Dimming, Switch Dimming
Emergency	Not Required, 3 Hours Facility

Product Code: AER