LEDUK **Bolt**

The Bolt LED is a linear luminaire which is 1184mm in length. It uses Philips LEDs to output 3400 lumens at 40 watts. The fitting is constructed from extruded pure aluminium which an anodised finish as standard or with a white powder coat as optional. The diffuser is made from high efficiency PMMA material located by machines aluminium endcaps. Available with 1-10V or DALI dimming.

- High transmittant frosted diffuser
- Philips Fortimo LED boards
- Instant on no flicker
- · Environmentally Friendly No mercury or lead enters the environment
- No RF and electronic magnetic interference

Ra>80

30.2 W 40.4 W

2617 lm 3429 lm

86.7 II/cW 84.9 II/cW

SKA Rating

Building Regulations

ETL (Energy Technology List) ECA (Enhanced Capital Allowance)

50,000 hours

• Over 50,000 hours life span

General

Performance

Colour Rendering

Longevity


System Power

Exit Lumens

Efficiency


Compliance

Dimensions	1184 x 52 x 90mm
Weight	3.2kg
Installation	Ceiling Surface Ceiling Suspended Wall Surface
Voltage	220-240Vac 50/60Hz
Certification	CE, ROHS
Warranty	3 Years











Available options

Wattage	30W - 2600 lm, 40W - 3400 lm
Colour Temperature	3000K, 4000K, 6000K
Mounting Option	Surface, Suspended
Dimming	Fixed output, 1-10V Dimming, DALI Dimming
Emergency	Not required, 3 Hour Emergency

Product Code: BLT