

LED UK

Circle HO

The Circle High Output LED is a large area circular luminaire available with a diameter of 950mm or 1500mm. The Circle can also be surface or suspended. The surface version has an LED backlighting kit which creates a halo effect on the ceiling. The fitting is made from roll formed aluminium with a Thermoelastic diffuser and has a fixingless minimalist appearance. Other custom sizes are available on request.



- Roll formed aluminium body
- Polycarbonate diffuser
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span

General

Dimensions	Ø950 x 140mm Ø1500 x 140mm
Weight	23.0 kg 36.0 kg
Installation	Ceiling Surface Ceiling Suspended
Voltage	90-250Vac 50/60Hz
Certification	CE, ROHS
Warranty	5 Years

Performance

Colour Rendering	Ra>80
Longevity	50,000 hours
System Power	88.0 W 206.0 W
Exit Lumens	7,000 lm 16,600 lm
Efficiency	79.5 ll/cW 80.6 ll/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating



Available options

Mounting Option	Surface, Suspended
Size	, Ø1500mm (206W)
Uplight	Not Required, Low Output
Colour	White, Aluminium, Special RAL
Colour Temperature	3000K, 4000K, 6000K
Dimming	Fixed Output, 1-10V Dimming, DALI Dimming
Emergency	Not Required, 3 Hour Emergency Facility, 3 Hour Emergency Facility (Non-Maintained), 3 Hour Emergency Facility (Self Test), 3 Hour Emergency Facility (Central Test)

Product Code: CIR-HO