

## **Draco A**

The Draco A LED is a 130mm diameter downlight which uses a CREE LED engine. The heatsink is constructed from die-cast aluminium complete with aluminium bezel and reflector. The Draco uses a high brightness twin reflector creating an anti-glare friendly cut-off. The bezel has 350° degrees of rotation with a 30° tilt. The Draco A is available in 960lm, 1,200 lm, and 1,600 lm outputs.

- CREE LED Engine
- Cast Aluminium
- Instant on no flicker
- Environmentally Friendly No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



## General

Dimensions	Ø130 x 155mm
Cutout	Ø120mm
Installation	Ceiling Tile Plasterboard
Beam Angle	15° 24° 30° 36° 45°
Voltage	AC220-240V
Certification	CE, ROHS
Warranty	5 Years





## **Performance**

Colour Rendering	Ra>80/90
Longevity	50,000 hours
System Power	12 W 15 W 20 W 25W
Exit Lumens	960 lm 1,200 lm 1,600 lm 2,000 LM
Efficiency	80.0 II/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating



## **Available options**

Wattage	12W - 960 lm, 15W - 1200 lm, 20W - 1600 lm, 25W - 2000lm
Colour	White, Special RAL Colour
Colour Temperature	3000K, 4000K, 5000K
Beam Angle	15° Beam, 24° Beam, 30° Beam, 36° Beam, 45° Beam
Dimming	Fixed Output, 1-10V Dimming, DALI Dimming, Mains Dimming, Switch Dimming
Emergency	Not Required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test

**Product Code: DRC-A-S**