LEDUK

HAZX Titan Mini

The HAZX Titan Mini luminaire is an explosion-proof CREE LED floodlight which can be used in Zone 1 & 2 (Gas) and Zone 21 & 22 (Dust). The luminaire is based on a dual chamber structure with the LED light sources and LED driver being housed separately for heat dissipation. The HAZX Titan Mini is finished with an epoxy powder coating with tempered glass lenses and stainless steel fixings.

- Zone 1 & 2 (Gas) & Zone 21 & 22 (Dust)
- Atex Certified
- CREE LED
- Honeycomb reflector for wide light distribution
- Excellent EMC compatibility
- Dual chamber design for integral gear and LEDs
- Over 60,000 hours life span




| Dimensions | 415 x 228 x 145mm |
|----------------|---|
| Weight | 8.3kg |
| Installation | Bracket Mounted |
| Voltage | 90-260Vac 50/60Hz |
| Classification | ExdII BT6 Gb/ExtIII BT85°C Db |
| Zone | Zone 1 & 2 (Gas) Zone 21 & 22 (Dust) |
| Warranty | 5 Years |




| IP rating | IP66 |
|------------------|--|
| Colour Rendering | Ra>80 |
| Longevity | 60,000 hours |
| System Power | 22.3 W 45.7 W 64.9 W |
| Exit Lumens | 1,657 lm 3,249 lm 5,037 lm |
| Efficiency | 74.3 II/cW 71.1 II/cW 77.6 II/cW |
| Compliance | ATEX Certified |











HAZX Titan Mini

Available options

| Wattage | 20W, 40W, 60W |
|----------------------------------|---|
| Colour Temperature | 3000K, 5000K |
| Beam Angle | 120° (Wide) |
| Lens Cover | Nickel Plated Steel, Stainless Steel |
| Emergency (Excludes 60W Version) | Not required, 3 Hour Emergency Facility |

Product Code: HAZX-TIN-M