

The Hestia LED is a 120mm diameter downlight which uses a CREE LED engine. The heatsink is constructed from die-cast aluminium complete with aluminium bezel and reflector recess detail creating a glare friendly cut-off which is also an aesthetically pleasing architectural detail.

- CREE LED Engine
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



General

| | |
|---------------|------------------------------|
| Dimensions | Ø120 x 101mm |
| Cutout | Ø110mm |
| Weight | 0.47kg |
| Installation | Ceiling Tile Plasterboard |
| Voltage | 220-240Vac |
| Certification | CE, ROHS |
| Warranty | 5 Years |

Performance

| | |
|------------------|--|
| Colour Rendering | Ra>82 |
| Longevity | 50,000 hours |
| System Power | 15W 20W |
| Exit Lumens | 1162 lm 1550 lm |
| Efficiency | 77.5 lm/cW |
| Compliance | Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating |

Available options

| | |
|--------------------|--|
| Wattage | 15W - 1162lm, 20W - 1550lm |
| Colour | White, Special RAL Colour |
| Colour Temperature | 3000K, 4000K, 6000K |
| Beam Angle | 15°, 24°, 36°, 60° |
| Lens | Polycarbonate |
| Dimming | Fixed Output, 1-10V Dimming , DALI Dimmable, Mains Dimming, Switch Dimming |
| Emergency | Not Required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test, Central Battery System |

Product Code: HST-S