

# LED UK

## Impact High Output

The IP65 Impact High Output LED is a vapour-proof luminaire with a IK10 Impact Rating which is available in 1500mm. The luminaire body is constructed from GRP and ABS which houses the singular LED board. The lens is part frosted reducing glare from all viewing angles.

- IP65 rated
- IK10 Impact Rating
- 1500mm modules
- 5 year warranty
- 50,000 hours
- Mercury free, No UV or IR
- Instant start and flicker free



### General

|               |  |
|---------------|--|
| Dimensions    | 1500 x 91 x 74mm                                     |
| Weight        | 4.5kg 1500mm Module                                  |
| Installation  | Ceiling Surface<br>Ceiling Suspended<br>Wall Surface |
| Voltage       | 200-240Vac 50/60Hz                                   |
| Certification | SAA, TUV, CE, GS, CB, ERP                            |
| Warranty      | 5 Years  |

### Performance

|                  |  |
|------------------|--|
| Colour Rendering | Ra>80-85   |
| Longevity        | 50,000 hours   |
| System Power     | 62.3 W   |
| Luminous         | 6230Lm   |
| Efficiency       | 100 lm/cW  |
| Compliance       | Building Regulations<br>ETL (Energy Technology List)<br>ECA (Enhanced Capital Allowance)<br>SKA Rating |

# Impact High Output

---

## Available options

|                    |  |
|--------------------|--|
| Wattage            | 60W (1500mm Module)  |
| Colour Temperature | 3000K, 4000K, 5000K, 6000K   |
| Mounting Option    | Surface, Suspended   |
| Microwave Sensor   | Not Required, Microwave Sensor   |
| Cable Entry        | Side Entries (IP68 connectors), Rear Entry   |
| Dimming            | Fixed Output, 1-10V Dimming, DALI, Switch Dimming  |
| Emergency          | Not required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test, 3 Hour Central Battery |

Product Code: IMP