


The Kleon LED is a Ø356 x 71mm surface ceiling/wall IP54 rated luminaire with outputs available from 1,200lm, to 2,300lm. The body is constructed from polycarbonate and has a white finish as standard. The diffuser is opal polycarbonate giving a pure uniform white appearance when the Kleon is illuminated.

- Polycarbonate body
- IP54 rated
- Instant on - no flicker
- No RF and electronic magnetic interference
- 50,000 hours life span


General

Dimensions	Ø356 x 71mm
Weight	1.0kg
Installation	Ceiling Surface Wall Surface
Voltage	100-240Vac
Certification	CE, ROHS
Warranty	5 Years
IP Rating	IP54



Performance

Colour Rendering	Ra>80
Longevity	50,000 hours
System Power	14.3 W 19.8 W 26.4 W
Exit Lumens	1,211 lm 1,724 lm 2,305 lm
Efficiency	84.7 l/W 87.1 l/W 87.3 l/W
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating



Available options

Wattage	14W - 1,200 lm, 20W - 1,700 lm, 26W - 2,300 lm
Colour	3000K, 4000K, 6500K
Microwave Sensor	Not Required, Microwave Sensor
Dimming	Fixed Output, 1-10V Dimming, DALI Dimming
Emergency	Not Required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test

Product Code: KLN