

LED UK

LED 30W-KAS-CL16R-M

Aluminum (AL01070) reflector of good reflection, PMMA lens with high transmittance, special designed PC cover for better lighting effect, wide selection of beam angles. This perfect design highlights optical quality and lighting quality, giving even and soft light, no dark dot, dark area and halo. Simple and elegant design concept, perfectly embodies its stability feature under gentle appearance, great visual comfort due to rear position of light source, Shading angle 30 degree, available in round and square versions. Anti-glare design, meets the standard of UGR19.



- CREE LED Engine
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span

General

| | |
|---------------|------------------------------|
| Dimensions | 140*138mm |
| Cutout | Ø120-130mm |
| Installation | Ceiling Tile Plasterboard |
| Beam Angle | 20° 24° 30° 36° |
| Voltage | AC220-240V |
| Certification | CE, ROHS |
| Warranty | 3 Years |

Performance

| | |
|------------------|---|
| Colour Rendering | Ra>80 |
| Longevity | 50,000 hours |
| System Power | 30 W |
| Exit Lumens | 2400 lm |
| Efficiency | 80.0 ll/cW |
| Compliance | Building Regulations ETL (Energy Technology List) ECA (Enhanced Carbon Allowance) SKA Rating |

Available options

| | |
|------------|--|
| Colour | 3000K, 4000K, 5000K |
| Beam Angle | 15° Beam, 24° Beam, 30° Beam, 36° Beam, 60° Beam |
| Dimming | Fixed Output, 1-10V Dimming, DALI Dimmable |

Product Code: LED 30W-KAS-CL16R-M