

LEX is an 85mm diameter recessed downlight that utilises a SHARP LED COB with an output of 575lm running at 9W. The heatsink is constructed from die-cast aluminium complete with a brushed aluminium front bezel. The heatsink features sprung arms which allows the fitting to be installed with ease. As standard LEX is both IP65 & Fire Rated (FR30, FR60 & FR90).

- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span
- Fire Rated + IP65



### General

Dimensions	Ø85 x 60mm
Cutout	Ø73mm
Weight	0.9kg
Beam Angle	36°
Installation	Ceiling Tile Plasterboard
Voltage	220-240Vac
Certification	CE, ROHS
Warranty	5 Years
IP Rating	IP65

### Performance

Colour Rendering	Ra>82
Longevity	50,000 hours
System Power	9W
Exit Lumens	575lm
Efficiency	63.8 lm/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

Available options

Wattage	9W
Colour	Aluminium (Brushed)
Colour Temperature	3000K, 4000K
Dimming	Fixed Output, 1-10V Dimming, DALI Dimming
Emergency	Not required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test

Product Code: LEX