


Linex is a surface mounted continuous extrusion luminaire available in 1000mm to 5000mm linear lengths or as prepared bespoke fitting for your project requirements. Linex is supplied with a Opal, Frosted or Clear diffuser which makes it ideal for architectural spaces. Linex Opal diffuser provides a dot free appearance across all wattages making the fitting suitable to be on display as an architectural feature. Linex is available as fixed output, dimmable or colour changing RGB.

- Aluminium profile
- Opal, Frosted or Clear polycarbonate diffuser
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span
- Supplied with Remote LED Driver
- Supplied with end caps & flying lead



### General

<b>Dimensions</b>	Height 15mm x Width 17mm
<b>Weight</b>	0.7 kg per metre
<b>Beam Angle</b>	90°
<b>Installation</b>	Surface Mounted
<b>Voltage</b>	220-240Vac
<b>Certification</b>	CE, ROHS
<b>Warranty</b>	5 Years



### Performance

<b>Colour Rendering</b>	Ra>80
<b>Longevity</b>	50,000 hours
<b>System Power</b>	5.00 W/m 7.20 W/m 10.0 W/m 15.0 W/m
<b>Lumens</b>	490 lm/m 750 lm/m 950 lm/m 1350 lm/m
<b>Compliance</b>	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

Available options

Length	1000mm, 2000mm, 3000mm, 4000mm, Bespoke
Body Finish	Aluminium, White, Black
Colour Temperature	2700K, 3000K, 4000K, 6000K, RGB, RGBW
Diffuser	Opal, Frosted, Clear
Wattage	5W/m, 7.2W/m, 10W/m, 15W/m
Dimming	Fixed Output, 1-10V Dimming, DALI Dimmable, Mains Dimming, Switch Dimming, DMX

Product Code: LNX