

MI Series - 4.8 mm Pixel Pitch

4.8 mm Pixel Pitch, Lightweight full colour LED Screen display

- Cabinet weight is only 8.3 kg, depth 73 mm, decreasing the transportation cost and the intensity of labour
- Super thin power supply inside; Quiet fan design, excellent heat dissipation, noiseless
- Refresh rate > 800HZ, 2 times higher than the regular screen, suitable for any occasion which requires much higher display capability
- The high polymer flexible mask can be pulled off directly from the cabinet, which makes the maintenance much more convenient
- Signal & power aviation connectors are water & dust proof, stable and reliable
- Cushion under the cabinet can protect the modules from being damaged
- Super-light aluminium alloy connectors are durable and artistic



| | |
|---|------------------------|
| Model | MI-SC-4.8 |
| Pixel Pitch (mm) | 4.8 |
| Physical Density (dot/m²) | 43,402 |
| LED Configuration | 1R1G1B |
| LED Type | SMD3528 |
| Module Size (mm x mm) | 240 x 240 |
| Module Resolution (PX x PX) | 50 x 50 |
| Power Consumption (W) | 60 |
| Drive Mode: | Constant Current Drive |
| Horizontal Viewing Angle (Deg) | 140 |
| Vertical Viewing Angle (Deg) | 140 |
| Brightness (cd/m²) | 1,200 |
| Grey Scale | 16 Bit |
| Refresh Rate (Hz) | 600/1920 |
| Cabinet Resolution (PX x PX) | 100 x 100 |
| Cabinet Max Power Consumption (W) | 300 |
| Cabinet Avg Power Consumption (W) | 120 |
| Cabinet Size (mm x mm) | 480 x 480 |
| Cabinet Weight (kg) | 7.5 |

MI Series - 4.8 mm Pixel Pitch

| | |
|------------------------------|----------------------|
| Cabinet Thickness (mm) | 73 |
| Cabinet Material | Aluminium |
| Colour | 281tn |
| Input Voltage | AC 110V~220V +/- 10% |
| Refresh Frame Frequency (Hz) | 60 |
| Protection Level | IP43 |
| Working Environemt | Indoor |
| Working Temperature (°C) | -20 ~ +40 |
| Operation Humidity (RH) | 10%-90% |
| Life Span (H) | 100,000 |
| Vertical Hanging Quantity | MAX 20 |
| Certificates | CE ETL TUV-EMC |

Product Code: MI-SC-4.8