

Phobos

The Phobos is a flexible surface downlight, it's adjustable angle lets you transform your lighting to suit your requirements. The luminaire has a 360° Rotation, and 0-90° tilt. It is available in Black, White, or Silver finish.

- Instant on no flicker
- Environmentally Friendly No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span




General

| Dimensions | 196 x 160 x 96mm |
|---------------|---------------------------------|
| Installation | Ceiling Surface |
| Beam Angle | 15° 20° 30° 36° 45° |
| Voltage | AC220-240V |
| Certification | CE, ROHS |
| Warranty | 5 Years |



Performance

| Colour Rendering | Ra>80/90 | |
|------------------|----------------------------------|--|
| Longevity | 50,000 hours | |
| System Power | 30 W | |
| | 35 W | |
| | 40 W | |
| | 50 W | |
| Exit Lumens | 2,700 lm | |
| | 3,150 lm | |
| | 3,600 lm | |
| | 4,200 lm | |
| Efficiency | 90.0 II/cW | |
| • | 90.0 II/cW | |
| | 90.0 II/cW | |
| | 84.0 II/cW | |
| Compliance | Building Regulations | |
| | ETL (Energy Technology List) | |
| | ECA (Enhanced Capital Allowance) | |
| | SKA Rating | |





Phobos

Available options

| Wattage | 30W - 2700 lm, 35W - 3150 lm, 40W - 3600 lm, 50W - 4200 lm |
|--------------------|--|
| Colour | White, Special RAL Colour |
| Colour Temperature | 3000K, 4000K, 5000K |
| Beam Angle | 15°, 20°, 30°, 36°, 45° |
| Dimming | Fixed Output, 1-10V Dimming, DALI Dimming, Mains Dimming, Switch Dimming |

Product Code: PHB