

LED UK

Plate

The Plate can be installed as an individual pendant or a component luminaire integrated into the 'Integra' System. The body is constructed from Aluminium with a PMMA diffuser. The Plate's LED array provides a uniformed, reduced glare & Dot free diffuser surface. The light distribution has a wide angle output providing both lighting functionality with an architectural finish. Drop rod dimensions are bespoke to your project requirements. Available in a white, black or aluminium finish.

- Range of Finishes
- Bespoke Rod Dimension
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



General

Dimensions	Ø300mm Ø600mm
Installation	Bespoke Fixed Rod Suspension
Voltage	100-240Vac 50/60Hz
Certification	CE, ROHS
Warranty	5 Years

Performance

Colour Rendering	Ra>80
Longevity	50,000 hours
System Power	18W 45W
Exit Lumens	1560 lm 3600 lm
Efficiency	86.66 lm/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

Available options

Size	300mm - 18W, 600mm - 45W
Colour	White, Black, Special RAL Colour
Colour Temperature	3000K, 4000K, 5000K
Installation	Suspended, Surface
Dimming	Fixed Output, 1-10V Dimming, DALI Dimming, Mains Dimming, Switch Dimming
Emergency	Not Required, 3 Hour Facility

Product Code: PLT