

LED UK

Ring 600

The Ring LED is a large area circular luminaire with a halo centre. The fitting is available in a diameter of 600mm. The Ring can also be surface or suspended. The body is made from roll formed aluminium and the diffuser is constructed from opal polycarbonate. The Ring has a fixingless minimalist appearance and is available in other custom sizes - available on request.



- Roll formed aluminium body
- Polycarbonate diffuser
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span

General

Dimensions	Ø600 x 105mm
Installation	Ceiling Surface Ceiling Suspended
Voltage	90-250Vac 50/60Hz
Certification	CE, ROHS
Warranty	5 Years

Performance

Colour Rendering	Ra>80
Longevity	50,000 hours
System Power	43.2 W
Exit Lumens	4,666 lm
Efficiency	108.0 l/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

LED UK

Ring 600

Available options

Mounting Option	Surface, Suspended
Size	Ø600mm (42.3 W)
Uplight	Not Required, Low Output
Colour	White, Aluminium, Special RAL Colour
Colour Temperature	3000K, 4000K, 6000K
Dimming	Fixed Output, 1-10V Dimming, DALI Dimming
Emergency	Not Required, 3 Hour Emergency Facility, 3 Hour Emergency Facility (Non-Maintained), 3 Hour Emergency Facility (Self Test), 3 Hour Emergency Facility (Central Test)

Product Code: RNG