

Sentinel Max Direct Indirect

Sentinel Max Direct Indirect is an IP65 architectural LED Pillar Light providing a wall mounted upwards and downwards output. Luminaire is constructed from a Die Cast Housing with a DuPont powder finish in White, Black or Grey. Fitting is available in 2 x 30W or 2 x 45W and is available with a choice of beam angles and LED colours.

- 304 Stainless Steel Fasteners
- 4mm Thick Tempered Glass
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span
- IP65

General

| | |
|---------------|----------------------|
| Dimensions | 350 x 180mm Diameter |
| Weight | 2.8 kg |
| Installation | Wall Mounted |
| Voltage | AC100-240 V |
| Certification | CE, ROHS |
| IP Rating | IP65 |

Performance

| | |
|------------------|--|
| Colour Rendering | Ra>0.80 |
| Longevity | 50,000 hours |
| System Power | 2 x 30 W 2 x 45 W |
| Exit Lumens | 2 x 2850 lm 2 x 4100 lm |
| Efficiency | 92 l/cW 92 l/cW |
| Compliance | Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating |

Available options

| | |
|--------------------|---|
| Wattage | 2 x 30W, 2 x 45W |
| Colour Temperature | 3000K, 4000K, 5000K |
| Body Finish | White, Black, Grey |
| Dimming | Fixed Output, 1-10 Dimming (Remote), DALI (Remote), Mains Dimming (Remote), Switch Dimming (Remote) |
| Emergency | Not Required, 3 Hour Facility (Remote), 3 Hour Self Test (Remote), 3 Hour Central Test (Remote) |

Product Code: STL-X-DI

