

Sentinel Max Square Direct Indirect

Sentinel Max Square Direct Indirect is an IP65 architectural LED Pillar Light providing a wall mounted upwards and downwards output. Luminaire is constructed from a Die Cast Housing with a DuPont powder finish in White, Black or Grey. Fitting is available in 2 x 30W or 2 x 45W and is available with a choice of beam angles and LED colours.

- 304 Stainless Steel Fasteners
- 4mm Thick Tempered Glass
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span
- IP65

General

Dimensions	350 x 150 x 150mm
Weight	2.8 kg
Installation	Wall Mounted
Voltage	AC100-240 V
Certification	CE, ROHS
IP Rating	IP65

Performance

Colour Rendering	Ra>0.80
Longevity	50,000 hours
System Power	2 x 30 W 2 x 45 W
Exit Lumens	2 x 2850 lm 2 x 4100 lm
Efficiency	92 l/cW 92 l/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

Available options

Wattage	2 x 30W, 2 x 45W
Colour Temperature	3000K, 4000K, 5000K
Body Finish	White, Black, Grey
Dimming	Fixed Output, 1-10 Dimming (Remote), DALI (Remote), Mains Dimming (Remote), Switch Dimming (Remote)
Emergency	Not Required, 3 Hour Facility (Remote), 3 Hour Self Test (Remote), 3 Hour Central Test (Remote)

Product Code: STQ-X-DI

