


Sirius IP Clear

The Sirius IP Clear LED is a 190mm diameter downlight which uses a CREE LED engine. The heatsink is constructed from die-cast aluminium complete with aluminium bezel and reflector. The heatsink features adjustable fold-out arms which allows the Sirius to be installed with ease. The luminaire is supplied with a clear diffuser giving the downlight an IP54 rating.

- CREE LED Engine
- IP54 Rating
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



General

Dimensions	Ø190 x 98mm
Cutout	Ø170mm
Weight	1.1kg
Beam Angle	90°
Installation	Ceiling Tile Plasterboard
Voltage	220-240Vac
Certification	CE, ROHS
Warranty	5 Years
IP Rating	IP54

Performance

Colour Rendering	Ra>82
Longevity	50,000 hours
System Power	15.9 W
Exit Lumens	1,600 lm
Efficiency	92.1 lm/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

LED UK

Sirius IP Clear

Available options

Wattage	15W - 1600 lm
Colour	White, Special RAL Colour
Colour Temperature	4000K
Bezel	Clear Lens
Dimming	Fixed Output, 1-10V Dimming, DALI Dimmable, Mains Dimming, Switch Dimming
Emergency	Not required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test

Product Code: SRS-S