

LED UK

Sirius IP Flat

The Sirius IP Flat LED is a 170mm diameter downlight which uses an SMD2835 Array. The heatsink is constructed from die-cast aluminium complete with aluminium bezel and reflector. The downlight is rated IP65.

- SMD 2835 LED Array
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span
- Rated IP65



General

Dimensions	Ø170 x 65mm
Cutout	Ø150mm
Weight	0.8kg
Beam Angle	120°
Installation	Ceiling Tile Plasterboard
Voltage	220-240Vac
Certification	CE, ROHS
IP Rating	IP65

Performance

Colour Rendering	Ra>82
Longevity	50,000 hours
System Power	20.0 W
Exit Lumens	2,000 lm
Efficiency	58.00 lm/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

Available options

Wattage	20W - 1700 lm
Colour	White
Colour Temperature	3000K, 4000K, 6000K
Dimming	Fixed Output, 1-10V Dimming, DALI Dimming, Mains Dimming, Switch Dimming
Emergency	Not Required, 3 Hour facility , 3 Hour Self Test, 3 Hour Central Test

Product Code: SRS-F