

Sirius New Plus

The Sirius LED is a 226mm diameter downlight which uses a Samsung SMD LED Array. The heatsink is constructed from die-cast aluminium complete with aluminium bezel and reflector. The heatsink features adjustable fold-out arms which allows the Sirius to be installed with ease. The downlight is available in outputs from 2500lm to 4400lm and as standard is rated IP65.

- SAMSUNG SMD LED
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span
- Rated IP65



General

Dimensions	Ø226 x 96mm
Cutout	Ø200mm
Weight	1.4kg
Beam Angle	90°
Installation	Ceiling Tile Plasterboard
Voltage	220-240Vac
Certification	CE, ROHS
Warranty	5 Years
IP Rating	IP65

Performance

Colour Rendering	Ra>82
Longevity	50,000 hours
System Power	30.0 W 40.0 W 50.0 W
Exit Lumens	2,500 lm 3,400 lm 4,400 lm
Efficiency	83.3 ll/cW 85.0 ll/cW 88.0 ll/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

Sirius New Plus

Available options

Wattage	30W - 2500 lm, 40W - 3400 lm, 50W - 4400 lm
Colour	3000K, 4000K, 5000K, 6000K
Bezel	Frosted Diffuser
Dimming	Fixed Output, DALI Dimmable, 1-10V Dimming
Emergency	Not required, 3 Hour Facility

Product Code: SRS-NP