

LED UK

Storm LED Tape

Storm is an IP68 rated self adhesive M3 LED Tape. The tape is available in 5m reel lengths. It has a 900 lm/m output with a power consumption of 13W/m and utiises 2835 60 LED chips p/mtr. Storm is supplied pre assembled up to 5Mts within increments of 100mm. It features low energy consumption with a high lumen output. The tape is flexible for installation indoor and outdoor use. Storm LED tape is available in a 10mm width and to ensure IP68 continuity is fitted with an IP 65 rated connection plug. Other bespoke cable lengths are available on request.



- IP68 rated
- 110° beam angle
- 69 lm/W
- 13 W/m
- 10m max. run length (details on request)
- Not suitable for submerssion into water
- Available 8mm or 10mm Wide

General

| | |
|-----------------|-----------------|
| Reel Length | 5m |
| Profile | 8x5mm or 10x5mm |
| Cutpoints | 100mm |
| LED Pitch | 16.6mm |
| Max. Single Run | 10m |
| Certification | CE, ROHS |
| Warranty | 5 Years |

Performance

| | |
|------------------|--------------|
| IP Rating | IP68 |
| Colour Rendering | Ra>80 |
| Longevity | 50,000 hours |
| Voltage | 24V |
| Power | 13.0 W/m |
| Exit Lumens | 900 lm P/Mtr |
| Efficiency | 70 lm/W |

Available options

| | |
|--------------------|--|
| Length | 1000mm, 2000mm, 3000mm, 4000mm, 5000mm, Bespoke |
| Colour Temperature | 2700K, 3000K, 4000K, 6000K, RGB, RGBW |
| Wattage | 10W, 15W |
| Dimming | Fixed Output, 1-10V Dimming, DALI Dimmable, Mains Dimming, Switch Dimming, DMX |

Product Code: SRM-TPE