

LED UK

Trend Surface Excell

Trend Architectural Spot Light is a surface mounted luminaire with an IP65 rating. The luminaire is constructed from Die Cast Aluminium and is available in varied wattages. Fitting is available in varied beam angles and LED colours.

- IP65 Rated
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span




General

| | |
|-----------------------|-------------------------------|
| Dimensions | 150mm Diameter x 245mm Height |
| Weight | 3.2 kg |
| Installation | Surface Mounted |
| Voltage | 120-277Vac |
| Operating Temperature | -30° + 55°C |
| Certification | CE, ROHS |
| Warranty | 5 Years |

Performance

| | |
|------------------|--|
| Colour Rendering | Ra>82 |
| Longevity | 50,000 hours |
| System Power | 42W |
| Exit Lumens | 4100 Lm |
| Beam Angles | 15°/24°/36° |
| Efficiency | 91.91 l/cW |
| Compliance | Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating |



Available options

| | |
|--------------------|---------------|
| Wattage | 42W |
| Beam Angle | 15°, 24°, 36° |
| Colour Temperature | 3000K, 4000K |
| Dimming | Fixed Output |

Product Code: TRX-SFC