

LED UK

Under Canopy Linear

The Under Canopy Linear LED is available in lengths of 600mm, 1200mm, and 1800mm. It is made from extruded aluminium with a frosted glass lens to achieve a highly efficient under canopy luminaire with integral gear fixed to the canopy.

- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



General

Dimensions	Ranging From: 600mm 1200mm 1800mm
Installation	Surface Mounted
Voltage	100-240Vac 50/60Hz
Certification	CE, ROHS
Warranty	5 Years

Performance

Colour Rendering	Ra>85
MacAdam Ellipse	3 Step
UGR	<19
System Power	Ranging From 15W 30W 45W
Exit Lumens	Ranging From 1,718 lm 3,435 lm 5,152 lm
Efficiency	114.5 ll/cW
Longevity	L90 / B10 @ 50,000 hours
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

LED UK

Under Canopy Linear

Available options

Size	600mm - 1,718lm, 1200mm -,3,435 lm, 1800mm - 5,152 lm
Colour Temperature	3000K, 4000K, 5000K
Dimming	DALI Dimming
Emergency	3 Hour Central Test

Product Code: UCL