

# LED UK

## Virdi Recessed Uplight

The Verdi is a 85mm diameter recessed uplight available 7 or 9 watt. It is constructed from stainless steel and tempered glass and is rated IP68. The fitting is supplied with a polycarbonate mounting sleeve and fitted with a low glare honeycomb louvre.



- IP68 Rated
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span

### General

Dimensions	Ø85 x 95mm
Cut Out	Ø72mm
Beam Angle	15° 24° 36° 45°
Voltage	24V
Certification	CE, ROHS

### Performance

Colour Rendering	Ra>80
Longevity	50,000 hours
System Power	7W 9W
Exit Lumens	450 Lm 611 Lm
Efficiency	50 l/cw 68 l/cw
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating



### Available options

Wattage	7 Watt, 9 Watt
Colour	Stainless Steel
Colour Temperature	2700K, 3000K, 4000K, 5000K
Diffuser	Honeycomb
Beam Angle	15° Beam, 24° Beam, 36° Beam, 45° Beam
Dimming	Not Required, 1-10V Dimming, DALI Dimmable, Mains Dimming, Switch Dimming
Emergency	Not Available

Product Code: VRU