

## **Alcor Mini Surface**

The Alcor Mini Surface is a Surface mounted compact luminaire finished in either Black or White. The fitting has a smooth finish and is available with a choice of beam angles, LED colours and lumen outputs. The Alcor uses a high quality die-cast aluminium heatsink for fast cooling to ensure performance and a long lifespan. This spotlight allows for a 350° horizontal rotation and a 0°-90° tilt for flexibility.

- · Instant on no flicker
- Environmentally Friendly No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span




## **General**

**Beam Angle** 

Dimensions50mm Diam x 144 L x 144 HInstallationSurface

15° 24° 36° 50°

VoltageAC220-240VCertificationCE, ROHSWarranty5 Years



## **Performance**

Colour Rendering Ra>82 Longevity 50,000 hours

 System Power
 7W

 Exit Lumens
 630

 Efficiency
 90.0 ll/cW

**Compliance** Building Regulations

ETL (Energy Technology List) ECA (Enhanced Capital Allowance)

SKA Rating

## **Available options**

| Wattage            | 7W - 630lm  |
|--------------------|---|
| Base Colour        | White, Black  |
| Colour Temperature | 3000K, 4000K  |
| Lens               | Clear, Honeycomb  |
| Beam Angle         | 15°, 24°, 36°, 50°  |
| Dimming            | Fixed Output, 1-10V Dimming, DALI Dimmable, Mains Dimming, Switch Dimming |

**Product Code: ALC-M-S**