

Astrix


The Astrix LED is a 90mm diameter downlight which uses a CREE LED engine. The heatsink is constructed from die-cast aluminium complete with aluminium bezel and reflector 30mm recess detail creating a glare friendly cut-off which is also an aesthetically pleasing architectural detail. The Astrix is available in 600lm and 700lm outputs with 15°, 24°, 30° and 36° beam angle options.

- CREE LED Engine
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span




General

Dimensions	Ø90 x 105mm
Cutout	Ø80mm
Weight	0.35kg
Installation	Ceiling Tile Plasterboard
Voltage	220-240Vac 100-240Vac
Certification	CE, ROHS
Warranty	5 Years



Performance

Colour Rendering	Ra>82
Longevity	50,000 hours
System Power	8.2 W 10.2 W
Exit Lumens	623 lm 747 lm
Efficiency	76.0 lm/cW 73.2 lm/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating



Available options

Wattage	8W - 623 lm, 10W - 747 lm
Colour	White, Special RAL Colour
Colour Temperature	3000K, 4000K, 6000K
Beam Angle	15° Beam, 24° Beam, 30° Beam, 36° Beam
Bezel	Clear Diffuser
Dimming	Fixed Output, 1-10V Dimming, DALI Dimming, Mains Dimming, Switch Dimming
Emergency	Not Required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test

Product Code: ASX-S