

Atlas Mini


The Atlas Mini is a 104mm diameter low void downlight which uses a Samsung LED engine. The heatsink is constructed from die-cast aluminium complete with aluminium bezel and reflector. The heatsink features spring arms which allows the downlight to be installed with ease. The Atlas Mini is available in outputs from 630lm, 910lm and 1,080lm outputs.

- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span




General

Dimensions	Ø104 x 25.8mm
Cutout	Ø90mm
Installation	Recessed
Beam Angle	90°
Voltage	AC220-240V
Certification	CE, ROHS
Warranty	5 Years



Performance

Colour Rendering	Ra>80
Longevity	50,000 hours
System Power	7 W 9 W 12 W
Exit Lumens	630 lm 910 lm 1,080 lm
Efficiency	90.0 lm/W
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating



Available options

Wattage	7W - 630 lm, 9W - 910 lm, 12W - 1,080 lm
Colour	White, Special RAL Colour
Colour Temperature	3000K, 4000K, 5000K
Dimming	Fixed Output, 1-10V Dimming, DALI Dimming, Mains Dimming, Switch Dimming
Emergency	Not Required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test

Product Code: ATS-M