

The Draco LED is a 183mm diameter downlight which uses a Cree XP-E LED Array. The heatsink is constructed from die-cast aluminium complete with aluminium bezel and polished reflector. The downlight is available in outputs from 1800lm to 3200lm and as standard is rated IP20.

- CREE LED Engine
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



General

Dimensions

Ø183 x 80mm

Cutout

Ø160mm

Installation

Ceiling Tile
Plasterboard

Beam Angle

30° / 45° / 80°

Voltage



AC220-240V

Certification

CE, ROHS

Warranty

5 Years



Performance

Colour Rendering

Ra>90

Longevity

50,000 hours

System Power

20 W

30 W

40 W

Exit Lumens

1,800 lm @4000K @30°

2,400 lm @4000K @30°

3,200 lm @4000K @30°

Efficiency

85.00 lm/cW

83.33 lm/cW

85.00 lm/cW

Compliance

Building Regulations

ETL (Energy Technology List)

ECA (Enhanced Capital Allowance)

SKA Rating

Available options

Wattage	20W - 1800 lm, 30W - 2400 lm, 40W - 3200 lm
Colour	White, Special RAL Colour
Colour Temperature	3000K, 4000K, 5000K
Beam Angle	35°, 45°, 80°
Dimming	Fixed Output, 1-10v Dimming, DALI Dimmable, Mains Dimming, Swith Dimming
Emergency	Not required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test, Central Battery System

Product Code: DRC-S