

Helios Range

The Helios Linear LED High Bay range is an aesthetically pleasing linear luminaire . The Helios is a 1200mm fitting available in 60W, 120W, 180W, 240W and 300W options. Ideal one-for-one replacement of conventional lighting systems such as HID and fluorescent.. Suitable for suspended installation only.

- Instant on no flicker
- Environmentally Friendly No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



General

98 x 287 x 1217mm
120°
Suspended
100-277Vac 50/60Hz
CE, ROHS
5 Years



Performance

Colour Rendering	Ra>80
Longevity	50,000 hours
System Power	60 W
	120 W
	180 W
	240 W
	300 W
Exit Lumens	6,000 lm
	12,000 lm
	18,000 lm
	24,000 lm
	30,000 lm
Efficiency	100 II/cW
Compliance	Building Regulations ETL (Energy Technology List)
	ECA (Enhanced Capital Allowance) SKA Rating



Helios Range

Available options

Wattage	60 W - 6,000 lm, 120 W- 12,000 lm, 180 W - 18,000 lm, 240 W - 24,000 lm, 300 W- 30,000 lm
Length	1200mm
Colour	3000K, 4000K, 6000K
Dimming	Fixed Output, 1-10V Dimming, DALI Dimmable
Emergency	Not required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test, Central Battery System

Product Code: HLS