Helios Range



The Helios Linear LED High Bay range is an aesthetically pleasing linear luminaire . The Helios is a 1200mm fitting available in 60W, 120W, 180W, 240W and 300W options. Ideal one-for-one replacement of conventional lighting systems such as HID and fluorescent.. Suitable for suspended installation only. .

- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



General

Dimensions	98 x 287 x 1217mm
Beam Angle	120°
Installation	Suspended
Voltage	100-277Vac 50/60Hz
Certification	CE, ROHS
Warranty	5 Years

Performance

Colour Rendering	Ra>80
Longevity	50,000 hours
System Power	60 W 120 W 180 W 240 W 300 W
Exit Lumens	6,000 lm 12,000 lm 18,000 lm 24,000 lm 30,000 lm
Efficiency	100 ll/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

LED UK

Helios Range

Available options

Wattage	60 W - 6,000 lm, 120 W- 12,000 lm, 180 W - 18,000 lm, 240 W - 24,000 lm, 300 W- 30,000 lm
Length	1200mm
Colour	3000K, 4000K, 6000K
Dimming	Fixed Output, 1-10V Dimming, DALI Dimmable
Emergency	Not required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test, Central Battery System

Product Code: HLS