

Honeycomb Lens Track Lighting

This LED is a 32.2mm diameter tracklight which uses a Epistar LED engine. This has an 1,800 lm output with a beam angle of either 30° or 50°.

- Epistar LED Engine
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



General

| | |
|----------------------|---|
| Dimensions | Ø100x90 mm (lamp) 120x85x45 mm (power box) |
| Installation | Track Integration |
| Voltage | 220-240Vac |
| Certification | CE, ROHS |
| Warranty | 5 Years |

Performance

| | |
|-------------------------|--|
| Colour Rendering | Ra>82 |
| Longevity | 50,000 hours |
| System Power | 20 W |
| Exit Lumens | 1800 lm |
| Efficiency | 90 lm/cW |
| Compliance | Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating |

Available options

| | |
|-------------------|--|
| Colour | 3000K, 4000K, 6000K |
| Beam Angle | 30° Beam, 50° Beam |
| Dimming | Fixed Output, DALI Dimmable, 1-10V Dimming |

Product Code: TRK-SPT-20