

## NI Series - 6.25 mm Pixel Pitch

6.25 mm Pixel Pitch, Indoor LED Floor Screens

- High loading support
- Rubber Seal
- Side-rubber(3 layers)
- New design buckle
- Bolts for taking-down modules
- Rubber seal (3 pcs)
- Fan-less heat sinking design
- Higher panel corners
- Adjustable base support+Aluminium place



|                                  |                      |
|----------------------------------|----------------------|
| <b>Model</b>                     | <b>NI-SC-6.25</b>    |
| <b>Pixel Pitch</b>               | 6.25mm               |
| <b>LED Configuration</b>         | SMD3528              |
| <b>Pixel Density</b>             | 25600/m <sup>2</sup> |
| <b>Unit Size(mm)</b>             | 500(W)×500(H)×82(D)  |
| <b>Unit Weight</b>               | 13kg                 |
| <b>Unit Resolution</b>           | 80*80                |
| <b>Module Size(mm)</b>           | 250(W)×250(H)        |
| <b>Module Resolution</b>         | 40*40                |
| <b>Scanning Mode</b>             | 1/8                  |
| <b>Brightness(cd/sqm)</b>        | ≥1500                |
| <b>Driver IC</b>                 | MBI5024/MY9269       |
| <b>Refresh Frequency</b>         | ≥720/≥2000           |
| <b>Max Power Consumption (W)</b> | 200/70               |
| <b>Avg Power Consumption</b>     | ≥12bit/≥16bit        |
| <b>Gray Scale</b>                | ≥14bit               |
| <b>View Angle</b>                | H140°/V140°          |
| <b>IP Level(front/rear)</b>      | IP65/IP65            |
| <b>Loading Capacity(/sqm)</b>    | 2000 kg              |



# NI Series - 6.25 mm Pixel Pitch

---

|                     |                   |
|---------------------|-------------------|
| Control System      | NOVA/DBSTAR/LINSN |
| Working Temperature | -30°C - +50°C     |
| Operating Humidity  | 10-90% RH         |

Product Code: NI-SC-6.25