


## Pike

The Pike LED is a 65mm diameter downlight which uses a CREE LED engine. The heatsink features adjustable fold-out arms which allows the Pike to be installed with ease.

- CREE LED Engine
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span

### General

|                      |                              |
|----------------------|------------------------------|
| <b>Dimensions</b>    | Ø65 x 79mm                   |
| <b>Cutout</b>        | Ø55mm                        |
| <b>Weight</b>        | 1.1kg                        |
| <b>Beam Angle</b>    | 15°<br>24°<br>30°<br>36°     |
| <b>Installation</b>  | Ceiling Tile<br>Plasterboard |
| <b>Voltage</b>       | 220-240Vac                   |
| <b>Certification</b> | CE, ROHS                     |
| <b>Warranty</b>      | 5 Years                      |



### Performance

|                         |                                                                                                        |
|-------------------------|--------------------------------------------------------------------------------------------------------|
| <b>Colour Rendering</b> | Ra>82                                                                                                  |
| <b>Longevity</b>        | 50,000 hours                                                                                           |
| <b>System Power</b>     | 8W                                                                                                     |
| <b>Exit Lumens</b>      | 593 Lumens                                                                                             |
| <b>Efficiency</b>       | 74.1 lm/cW                                                                                             |
| <b>Compliance</b>       | Building Regulations<br>ETL (Energy Technology List)<br>ECA (Enhanced Capital Allowance)<br>SKA Rating |

Available options

|                    |                                                                          |
|--------------------|--------------------------------------------------------------------------|
| Wattage            | 8W - 593 lm                                                              |
| Colour             | White, Special RAL Colour                                                |
| Colour Temperature | 2700K, 3000K, 4000K, 5000K                                               |
| Beam Angle         | 15°, 24°, 30°, 36°                                                       |
| Lens               | Clear                                                                    |
| Dimming            | Fixed Output, 1-10V Dimming, DALI Dimming, Mains Dimming, Switch Dimming |
| Emergency          | Not required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test     |

Product Code: PKE-S