

LED UK

Plutus Single

The Plutus Single LED is a 180 x 190mm gimbal recessed downlight using CREE LED engines. The gimbal LED head is mounted in a steel box housing with black internal finish. The LED head has a 30° x 30° range. The bezel has a deep recess detail creating a glare friendly cut-off which is also an aesthetically pleasing architectural detail.

- CREE LED Engine
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span
- Dimming Options



General

| | |
|---------------|------------------------|
| Dimensions | 190 x 190 x 176mm |
| Cutout | 160 x 160mm |
| Weight | 0.85kg |
| Installation | Recessed |
| Voltage | 220-240 Vac 110 Vac |
| Certification | CE, ROHS |
| Warranty | 5 Years |

Performance

| | |
|------------------|--------------|
| Colour Rendering | Ra>80 |
| Longevity | 50,000 hours |
| System Power | 32.7 W |
| Exit Lumens | 2,510 lm |
| Efficiency | 76.8 ll/cW |

Available options

| | |
|--------------------|--|
| Colour Temperature | 3000K, 4000K, 5000K |
| Beam Angle | 15°, 24°, 60° |
| Dimmable | Fixed Output, 1-10V Dimming, DALI Dimmable |

Product Code: PLT-S-30