


Stark Mini Frosted

The Stark Mini IP LED is a 130mm diameter surface mounted downlight which uses a CREE LED engine. The heatsink is constructed from die-cast aluminium complete with aluminium rolled-formed body and reflector. The base plate uses three fixing points with a twist and lock action to secure the luminaire on the ceiling. The bezel has a deep recess detail creating a glare friendly cut-off which is also an aesthetically pleasing architectural detail. The Stark Mini IP is available in 900 and 1200 lumen outputs with a 90° beam angle.

- CREE LED Engine
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span

General

Dimensions	Ø130 x 100mm
Weight	0.3kg
Installation	Ceiling Surface Ceiling Suspended
Voltage	220-240Vac
Certification	CE, ROHS
Warranty	5 Years



Performance

IP Rating	IP42
Colour Rendering	Ra>82
Longevity	50,000 hours
System Power	12 W 15 W
Exit Lumens	900lm 1200lm
Efficiency	75.0 ll/cW 80.0 ll/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

Stark Mini Frosted

Available options

Wattage	12 W - 900lm, 15 W - 1200lm
Colour	White, Special RAL Colour
Colour Temperature	3000K, 4000K
Lens	Frosted
Beam Angle	90°
Mounting Option	Surface, Suspended
Dimming	Fixed Output, 1-10V Dimming, Dali Dimming, Mains Dimming, Switch Dimming
Emergency	Not required, 3 Hour Facility, 3 Hour Self Test, 3 Hour Central Test

Product Code: STK-M