

The Topaz LED downlight has a 70mm diameter bezel whilst using a CREE LED engine. The heatsink is constructed from die-cast aluminium complete with aluminium bezel and reflector. The bezel features a recess detail creating a glare friendly cut-off which is also an aesthetically pleasing architectural detail.

- CREE LED Engine
- Cast Aluminium
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span



General

Dimensions	Ø70 x 75mm
Cutout	Ø65mm
Weight	0.7kg
Installation	Ceiling Tile Plasterboard
Voltage	220-240Vac 100-240Vac
Certification	CE, ROHS
Warranty	5 Years

Performance

Colour Rendering	Ra>82
Longevity	50,000 hours
System Power	8.2 W
Exit Lumens	622 lm
Efficiency	75.9 ll/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

Available options

Wattage	8W - 600 lm
Colour	2700K, 3000K, 4000K, 5000K
Beam Angle	15° Beam, 24° Beam, 30° Beam, 36° Beam, 60° Beam, 80° Beam
IP Rating	IP20 Rated, IP44 Rated
Lens	Clear Lens, Frosted Lens
Body	Fixed, Adjustable
Dimming	Fixed Output, 1-10V Dimmable, DALI Dimmable, Mains Dimmable
Emergency	Not required, 3 Hour Facility

Product Code: TPZ