

Trend Hood Spike

Trend Hood Spike Architectural Spot Light is a surface mounted luminaire with an IP65 rating. The luminaire is constructed from Die Cast Aluminium and is available in varied wattages. The fitting is available in a 25° beam angle. The fitting is supplied with an in-ground mounting spike and LED drivers are mounted integrally to the fitting. An optional 'ABS' spike is also available with this fitting.

- IP65 Rated
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span
- Integral Mounted LED Driver



General

| | |
|------------------------------|-------------------------------|
| Dimensions | 130mm Diameter x 410mm Height |
| Weight | 1.7 Kg |
| Installation | Spike Mounted |
| Voltage | 120-277Vac |
| Operating Temperature | -30° + 55°C |
| Certification | CE, ROHS |
| Warranty | 5 Years |

Performance

| | |
|-------------------------|--|
| Colour Rendering | Ra>82 |
| Longevity | 50,000 hours |
| System Power | 10W 15W |
| Exit Lumens | 630 Lm 950 Lm |
| Beam Angles | 25° |
| Efficiency | 63.33 l/cW |
| Compliance | Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating |

Available options

| | |
|---------------------------|--------------|
| Wattage | 10W, 15W |
| Beam Angle | 25° |
| Colour Temperature | 3000K, 4000K |
| Dimming | Fixed Output |

Product Code: TRH-SPK