

## Trend Hood Spike

---

Trend Hood Spike Architectural Spot Light is a surface mounted luminaire with an IP65 rating. The luminaire is constructed from Die Cast Aluminium and is available in varied wattages. The fitting is available in a 25° beam angle. The fitting is supplied with an in-ground mounting spike and LED drivers are mounted integrally to the fitting. An optional 'ABS' spike is also available with this fitting.

- IP65 Rated
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span
- Integral Mounted LED Driver



### General

<b>Dimensions</b>	130mm Diameter x 410mm Height
<b>Weight</b>	1.7 Kg
<b>Installation</b>	Spike Mounted
<b>Voltage</b>	120-277Vac
<b>Operating Temperature</b>	-30° + 55°C
<b>Certification</b>	CE, ROHS
<b>Warranty</b>	5 Years

### Performance

<b>Colour Rendering</b>	Ra>82
<b>Longevity</b>	50,000 hours
<b>System Power</b>	10W 15W
<b>Exit Lumens</b>	630 Lm 950 Lm
<b>Beam Angles</b>	25°
<b>Efficiency</b>	63.33 l/cW
<b>Compliance</b>	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

### Available options

<b>Wattage</b>	10W, 15W
<b>Beam Angle</b>	25°
<b>Colour Temperature</b>	3000K, 4000K
<b>Dimming</b>	Fixed Output

**Product Code: TRH-SPK**