

Trend Hood Spike

Trend Hood Spike Architectural Spot Light is a surface mounted luminaire with an IP65 rating. The luminaire is constructed from Die Cast Aluminium and is available in varied wattages. The fitting is available in a 25° beam angle. The fitting is supplied with an in-ground mounting spike and LED drivers are mounted integrally to the fitting. An optional 'ABS' spike is also available with this fitting.

- IP65 Rated
- Instant on - no flicker
- Environmentally Friendly - No mercury or lead enters the environment
- No RF and electronic magnetic interference
- Over 50,000 hours life span
- Integral Mounted LED Driver

General

Dimensions	130mm Diameter x 410mm Height
Weight	1.7 Kg
Installation	Spike Mounted
Voltage	120-277Vac
Operating Temperature	-30° + 55°C
Certification	CE, ROHS
Warranty	5 Years

Performance

Colour Rendering	Ra>82
Longevity	50,000 hours
System Power	10W 15W
Exit Lumens	630 Lm 950 Lm
Beam Angles	25°
Efficiency	63.33 l/cW
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

Available options

Wattage	10W, 15W
Beam Angle	25°
Colour Temperature	3000K, 4000K
Dimming	Fixed Output

Product Code: TRH-SPK

