

Union Floodlight

The floodlight is constructed from high grade cast aluminium finished with a zinc coating for interior and exterior use. The highly efficient Cree LED light source creates exit lumen packages ranging from 3600 to 32400lm

- Cree LED chips
- 50,000hours
- 3000K, 4000K & 6000K
- DALI / 0-10Vdc dimming
- Photocell sensor system
- Built-in surge protection
- Built-in thermal protection
- Maintenance free
- Mercury free, No UV or IR
- Instant start and flicker free
- Patent multi-function design
- Up to 10 year warranty

General

Dimensions	360 x 358 x 187mm
Weight	8 kg
Certification	SAA, TUV, CE, GS, CB, ERP
Warranty	Up to 10 Years

Performance

Operating Temperature	-40°C - 60°C
Colour Rendering	Ra>80
Longevity	50,000 hours
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating

Available options

Wattage	30W, 60W, 90W, 120W, 150W, 180W, 210W, 270W
Colour Temperature	Warm White (3000K), Neutral White (4000K), Cool White (6000K)
Beam Angle	60°, 120°, 140 X 60°
IP Rating	IP65, IP67
Mounting Option	Pendent, Pole, Bracket
Dimming	Fixed Output, 1-10V Dimmable, DALI Dimmable
Photocell	Not Required, Microwave Sensor, Photocell
Input	80 - 315Vac, 80 - 400Vdc
Light Distribution	No Beam Control, Lens Guard

Product Code: UNI

