Union Max Projector

The Single Lens Projector is constructed from high grade cast aluminium finished with a zinc coating for interior and exterior use. The highly efficient Cree LED light source creates exit lumen packages ranging from 24,000 to 84,000lm.



- Cree LED chips
- 50,000hours
- 3000K, 4000K & 6500K
- DALI / 0-10Vdc dimming
- Photocell sensor system
- Built-in surge protection
- Built-in thermal protection
- Maintenance free
- Mercury free, No UV or IR
- Instant start and flicker free
- Patent multi-function design
- Up to 10 year warranty


General



Dimensions	466 x 388 x 471mm
Weight	19.0 kg
Certification	SAA, TUV, CE, GS, CB, ERP
Warranty	Up to 10 Years

Performance

Operating Temperature	-40°C - 60°C
Colour Rendering	Ra>80
Longevity	50,000 hours
Compliance	Building Regulations ETL (Energy Technology List) ECA (Enhanced Capital Allowance) SKA Rating



LED UK

Union Max Projector

Available options

Wattage	300W, 400W, 500W, 600W, 700W
Colour Temperature	Warm White (3000K), Neutral White (4000K), Cool White (6000K)
Beam Angle	15°, 20°, 30°
IP Rating	IP67
Mounting Option	Pendent, Pole, Bracket
Dimming	Fixed Output, 1-10V Dimmable, DALI Dimmable
Photocell	Not Required, Microwave Sensor, Photocell
Input	110-480Vac
Light Distribution	No Beam Control, Horizontal Hood, Lens Guard, Horizontal Hood + Lens Guard

Product Code: UNI